

Zeitverluste			
	Stromstärke	Leistung	Wirkungsgrad
3-phasig	11,4 A	2500 W	32%
	12,0 A	4400 W	53%
	12,6 A	5400 W	63%
	13,0 A	6200 W	69%
	16,0 A	9200 W	83%
	32,0 A	21900 W	99%
1-phasig	8,0 A	1310 W	71%
	9,0 A	1490 W	75%
	10,0 A	1800 W	81%
	11,0 A	2060 W	85%
	12,0 A	2280 W	87%
	13,0 A	2630 W	91%
	14,0 A	2930 W	93%
	15,0 A	3100 W	93%
	16,0 A	3510 W	95%
	17,0 A	3830 W	96%
	18,0 A	3940 W	97%
	19,0 A	4200 W	97%
	20,0 A	4500 W	97%
	21,0 A	4620 W	98%
	22,0 A	5010 W	99%
	23,0 A	5210 W	99%
	24,0 A	5420 W	99%
	25,0 A	5670 W	99%
	26,0 A	5990 W	99%
	27,0 A	6100 W	99%
	28,0 A	6340 W	99%
	29,0 A	6620 W	99%
	30,0 A	6770 W	99%
	31,0 A	7100 W	99%
	32,0 A	7110 W	99%

Energieverluste >13 A (1-phasig)		
	Batteriestand bei Ladestart	Wirkungsgrad
	5%	80%
	10%	80%
	15%	79%
	20%	79%
	25%	78%
	30%	78%
	35%	77%
	40%	76%
	45%	75%
	50%	73%
	55%	72%
	60%	70%
	65%	68%
	70%	65%
	75%	62%
	80%	58%
	85%	51%
	90%	42%
	95%	28%